

Institut für Regelungs- und Steuerungssysteme Prof. Dr.-Ing. Mike Barth Fritz-Haber -Weg, Geb. 30.33 76131 Karlsruhe | www.irs.kit.edu



Simulation of a soft robot with gazebo

Abstract

Bachelorthesis at IRS-VSA. During this thesis, a simulation of a soft robot based on the piece-wise constant curvature model should be developed.

Start: 08.01 Tags: Robotics, Soft Robotics, PCC, Simulation



Supervisor: Linus Witucki, M. Sc.

IRS-VSA, Raum 212 Tel.: 0721/608-42628 linus.witucki@kit.edu

Motivation

Human-robot collaboration is increasingly becoming a crucial area of research within the context of Industry 4.0. It promises to combine the repeatability and precision of robots with the flexibility and decision-making skills of humans. Therefore, robots are being developed that are small, light and have torque sensors implemented to make them safe for close physical coupling with humans. But the safety is only guaranteed through the sensors and software. In a fail-state, the robot can still harm the human. As a result, a completely new kind of robot emerged, the soft robot. These robots are developed with the safety by design concept in mind. Mostly, they consist of soft materials like cloth or silicon and are actuated pneumatically instead of with motors. Such robots are inherently safe for direct human-robot coupling. An example of a soft robot can be seen in Figure 1. To make the deployment of these robots easier simulation tools are required. One such simulation should be developed during the course of this thesis.




Figure 1: Soft robot @Festo

Goal

The goal of the thesis is to develop a modular kinematic simulation of a soft robot. For this, a piece-wise constant curvature model of the robot can be applied. Which means, the robot consists of multiple segments and each segment has the constraint of a constant curvature (see Figure 2). As a software framework, ROS2 in combination with Gazebo are a great starting point.

Helpful prior knowledge

The subsequent prior knowledge is advantageous for the completion of the final thesis:

1

- Soft Robotics
- Robotics
- ROS2
- Gazebo




Figure 2: Piece-wise constant curvature



Figure 3: Gazebo



Institut für Regelungs- und Steuerungssysteme Prof. Dr.-Ing. Mike Barth Fritz-Haber -Weg, Geb. 30.33 76131 Karlsruhe | www.irs.kit.edu



Work packages

Work package 1: Research

- Research in soft robotics
 - Soft robot
 - Piece-wise constant curvature model
 - Control strategies for soft robots
- WP-Results:
 - Detailed summary about existing soft robot projects

Work package 2: ROS2

- At least 2 ROS2 training tutorials
- ROS2 example projects
- WP-Results:
 - List of completed ROS2 tutorials

Work package 3: Software architecture

- Design of the software architecture that will be used for the implementation
- WP-Results:
 - Detailed report explaining the software architecture
 - UML diagrams of the software architecture

Work package 4: Implementation

- Implementation of the designed software architecture
- WP-Results:
 - Simulation results
 - Comparison with state of the art research